


TRANTEX MODEL CH360SPS

SELF-PROPELLED SPRAY THERMOPLASTIC APPLICATOR



STANDARD EQUIPMENT

- SELF PROPULSION SYSTEM** • Hydrostatic drive allows infinite speeds, forward and reverse, of up to 4 mph (7 kph).
- DRIVE ENGINE** • 5.5 HP propane fired Honda.
- AIRLESS SPRAY DEVICES** • 4", 6", 8", or 12" airless spray guns available.
Spray thicknesses: 25 mils. (.6mm) - 125 mils. (3.0mm)
- VARIABLE WIDTH GLASS BEAD SYSTEM** • Bead hopper capacity of 60 lbs. Adjustable widths of 4", 8", 12", and dual 4".
- 360 LB. MATERIAL TANK CAPACITY** • Removable/interchangeable for quick color changes.
- AUTOMATIC AGITATION SYSTEM** • Continuous agitation of molten material.
- AUTOMATIC THERMOSTAT** • Regulates material temperature automatically.
- HAND TORCH** • Standard for numerous operations.
- POINTER SYSTEM** • Adjustable, lift/lower.
- TOOL KIT** • Standard
- COMPACT SIZE** • Weight - 600 lbs.



OPTIONAL EQUIPMENT

- OPERATOR'S SULKY** • Adjustable padded seat provides additional propane storage. Can be removed in seconds for detail work. Includes unique steering system that allows for straight steering or preset radii in curves.
- EXTRA MATERIAL TANK** • Allows on the spot color changes.
- DOUBLE DROP GLASS BEAD SYSTEM** • For improved luminosity.



Trantex supplies a complete line of thermoplastic and paint equipment and materials. Contact us today for a free catalog!

**NEW!
DUAL 4"
SPRAY DEVICE**



4", 6", 8", 12" and dual 4"
Airless Spray Devices.



Line widths are easily
changed in seconds.